

TOMINGLEY GOLD MINE

Monthly Environmental Monitoring Report

November 2023

TOMINGLEY GOLD MINE

Monthly Environmental Monitoring Report

November 2023

Document History

Date	Version	Reason For Change	Author
	1	Submitted for Information	LM

Table of Contents

1. INTRODUCTION AND SCOPE	4
2. WEATHER STATION DATA	4
3. MONITORING LOCATIONS	5
4. AIR QUALITY MONITORING.....	6
A. TEOM PM ₁₀ Particulates Monitoring	6
B. Depositional Dust	7
C. High Volume Air Sampler - Total Suspended Particulates.....	8
5. NOISE MONITORING.....	8
6. SURFACE WATER MONITORING	8
A. RSF and Wyoming Central Dam.....	9
B. Sedimentation Basins	9
C. Gundong Creek	9
7. GROUNDWATER MONITORING	9
8. BLAST MONITORING.....	10
9. BIODIVERSITY MONITORING	10

1. Introduction and Scope

This Monthly Environmental Monitoring Report has been prepared to collate environmental monitoring data undertaken for the Tomingley Gold Operation (TGO) during the month of November 2023.

This report also compares data collected to targets and provides commentary on environmental issues during the month.

2. Weather Station Data

TGO operates a permanent weather monitoring station. This weather station provides the mine site with continuous real-time data. Reporting requirements as stipulated in EPL 20169 include wind direction and wind speed at 10 metres **Figure 1** and rainfall mm **Table 1**.

Figure 1. TGO Wind Rose




Figure 3.4: Tomingley Gold Operations Site - Windrose


Table 1: TGO Rainfall Data

November 2023	Rainfall (mm)	Year to Date
Total Rainfall	152.0 mm	583.2 mm

3. Monitoring Locations

Figure 2 indicates the location of where monitoring is undertaken for the project. Any additional monitoring undertaken will be discussed within the body of this report.

Figure 2. TGO Environmental Monitoring Sites



4. Air Quality Monitoring

A. TEOM PM₁₀ Particulates Monitoring

PM₁₀ is measured via a Tapered Element Oscillating Microbalance (TEOM) located at the southern edge of the Tomingley Village. This machine transmits real-time data via the internet to a computer located on site.

TGO monitor and report on compliance with the air quality conditions stipulated in TGO's Project Approval: Tomingley Gold Project. Impact assessment criteria as stipulated in the PA refers to any residence on privately-owned land or on more than 25 percent of any privately-owned land. Refer to **Tables 2 & 3** for conditions pertaining to TEOM monitoring.

Table 2: Long term impact assessment criteria for particulate matter

<i>Pollutant</i>	<i>Averaging Period</i>	<i>Criterion^d</i>
Total suspended particulate (TSP) matter	Annual	a 90 µg/m ³
Particulate matter < 10 µm (PM ₁₀)	Annual	a 25 µg/m ³
Particulate matter < 2.5 µm (PM _{2.5})	Annual	a 8 µg/m ³

Table 3: Short term impact assessment criterion for particulate matter

<i>Pollutant</i>	<i>Averaging Period</i>	<i>Criterion^d</i>
Particulate matter < 10 µm (PM ₁₀)	24 hour	a 50 µg/m ³
Particulate matter < 2.5 µm (PM _{2.5})	24 hour	a 25 µg/m ³


Table 4: Long term impact assessment criteria for deposited dust

<i>Pollutant</i>	<i>Averaging Period</i>	<i>Maximum increase in deposited dust level</i>	<i>Maximum total deposited dust level</i>
Deposited dust ^c	Annual	2 g/m ² /month ^b	4 g/m ² /month ^{a, d}

Notes to Tables

- a* Total impact (ie incremental increase in concentrations due to the project plus background concentrations due to all other sources);
- b* Incremental impact (ie incremental increase in concentrations due to the project on its own);
- c* Deposited dust is to be assessed as insoluble solids as defined by Standards Australia, AS/NZS 3580.10.1:2016: Methods for Sampling and Analysis of Ambient Air - Determination of Particulate Matter - Deposited Matter - Gravimetric Method, or its latest version; and
- d* Excludes extraordinary events such as bushfires, prescribed burning, dust storms, sea fog, fire incidents or any other activity agreed by the Secretary.

Figure 3. TGO TEOM Data



B. Depositional Dust

Depositional Dust monitoring undertaken during this month returned the results shown in **Table 5** below. There was one exceedance for this monitoring period. Refer to **Table 4** for conditions pertaining to depositional dust monitoring.

It is believed that the exceedance during this month was an anomaly partly caused by ongoing road works (grading of an unsealed road) and agricultural activities (ploughing) in the vicinity of the dust monitor. It is noted that only a single dust gauge was impacted. The elevated results this month are also substantially above the long-term average for the site. TGO will continue to monitor activities around the dust gauge, but do expect results to return to normal by the next completion of the next round of monitoring.

Table 5: Dust Deposition Results

Location	Dates Monitored	Total Insoluble Matter (g/m ² /month)	Total Insoluble Matter (g/m ² /month) YTD Average	Complies
DDG1	06/11/2023 – 01/12/2023	2.1	0.83	Y
DDG2		2.6	1.06	Y
DDG3		1.2	0.62	Y
DDG4		1.5	2	Y
DDG5		6.1	1.56	Y

C. High Volume Air Sampler - Total Suspended Particulates

One High Volume Air Sampling (HVAS) unit has been installed in Myall Street, Tomingley, (in the yard of the closest receptor) just north of the Project site. The HVAS measures Total Suspended Particulates (TSP) on a 24-hour, one-day-in-six frequency and is co-located with the TEOM. **Table 6** below provides the results.

The performance criteria for TSP are averaged over 12 months.

Table 6: Hi-Volume Air Sampler Results

Location	Sample Date	Results (TSP $\mu\text{g}/\text{m}^3$)	Year to Date Average (TSP $\mu\text{g}/\text{m}^3$)	Performance Criteria (Annual Average)	Complies
HVAS1	06/11/2023	98	37.83 $\mu\text{g}/\text{m}^3$	90 $\mu\text{g}/\text{m}^3$	Y
HVAS1	12/11/2023	43.7			
HVAS1	18/11/2023	48.2			
HVAS1	24/11/2023	14.0			
HVAS1	30/11/2023	9.2			

5. Noise Monitoring

TGO uses a combination of real-time and attended monitoring to evaluate the performance of the project. For monitoring locations see **Figure 2**.

A review of monitoring data and operator attended observations determined that TGO contributions did not exceed relevant limits during applicable meteorological conditions. A full report is provided separately on the Alkane webpage.

6. Surface Water Monitoring

TGO undertakes water quality monitoring at several locations within and surrounding the site. Water quality monitoring locations (**Figure 2**) include those locations specified in EPL 20169, as well as additional sampling locations. The intent of the surface water monitoring program is to ensure that the water quality impacts associated with the mining operations are minimised.

EPL 20169 requires that surface water quality be monitored at two locations within the process water system (RSF) and (Wyoming Central Dam); six locations within the dirty water system (Sediment Basins); and two locations within the surrounding clean water system (Gundong Creek).

A. RSF and Wyoming Central Dam

The required monitoring frequency for both points is daily during discharge. TGO monitor for Cyanide (weak acid dissociable (WAD)) with a 90-percentile concentration limit of 20mg/L and 100-percentile concentration limit of 30mg/L.

WAD cyanide discharge levels for the month are summarised below.

- Monthly average: 3.33 mg/L
- Daily maximum: 5.632 mg/L
- Daily minimum: 0.414 mg/L

Samples assessed during the month were within guidelines.

B. Sedimentation Basins

TGO's six sediment basins are licenced discharged points. EPL 20169 monitoring frequency for these sediment basins is during discharge.

C. Gundong Creek

Due to the ephemeral nature of Gundong Creek, water quality sampling opportunities are limited. Gundong Creek does not provide a secure water supply either for human consumption or agricultural purposes. Gundong Creek may however provide additional irrigation and stock water. TGO's PA requires baseline water trigger levels to be maintained or improved.

Sample results for the month were within guidelines.

7. Groundwater Monitoring

TGO undertake quarterly groundwater monitoring in line with EPL and PA requirements. The purpose of the groundwater monitoring program is to provide a framework for monitoring and management of groundwater quality and levels. Results are reported in TGO's Annual Review which is made available to the public on the Alkane webpage.

8. Blast Monitoring

TGO operate to the blasting criteria as stipulated in our EPL and PA. These conditions include airblast overpressure, ground vibration, frequency. Refer to **Table 7** below for Project Approval conditions pertaining to blast monitoring.

Table 7: Blasting Criteria

Location	Airblast Overpressure (dB(Lin Peak))	Ground Vibration (mm/s)	Allowable Exceedance
Residence on privately owned land	120	10	0%
	115	5	5% of total blasts over any 12 month period
All public infrastructure	Nil limit	50	0%
RSF 1 and RSF 2 embankments	Nil limit	49	RSF 1 and RSF 2 embankments

However, apart from the limit on the RSF1 and RSF 2 embankments, these criteria do not apply if the Proponent has a written agreement with the relevant landowner, and has advised the Department in writing of the terms of this agreement.

Blasts that trigger the monitoring equipment are recorded and the data is retained on site. There were no blast exceedances during the month.

9. Biodiversity Monitoring

TGO are required to report any incident of death or injury (including bogging or miring) of fauna (avian or terrestrial) associated with the RSF as stipulated in EPL 20169.

Reportable fauna incidents:

- No reportable incidents were recorded during the month.